



# DVR Model 484816 H



## Specification

- CPU/ RAM/ VGA Min of 2.5GHz Pentium4 / 2Gb or more / Intel
- Operating System Windows XP / Vista / Windows 7
- HDD 250Gb / 500Gb / 1Tb / 1.5Tb / 2Tb / Custom
- Sound Card On Board
- Network Card On Board
- Graphics Card On Board or Radian 9000 or higher
- CD-RW/DVD Installed
- Camera Input 16 CH / 32 CH ( BNC Type NTSC/PAL
- Sound Input 16 CH / 32 CH
- Screen Partition Multi -View 1, 4, 6, 9, 10, 16, 32
- Display Speed 480fps
- Recording Speed 480fps
- Resolution 704x480; 704x240; 325x240
- Recording Mode Motion Detection/Schedule/Continuously/Sensor Recording speed setup for each camera, including day of the week and time recorded .
- Sensor Input 16/32 channel sensor input (option)
- Sound Recording 16/32CH Supports two-way voice communication
- Supports Watchdog Automatic system restoration on system failure
- Compression Type H.264 Hardware compression
- Compression file Size 1.5kb-20kb
- Dynamic IP Supporting
- E-mail Event Alert Select
- LAN 10/100/1000
- Remote Control Remote Pan / Tilt / Zoom / Focus/Iris Control / Auto Panning/ Preset Control/ Remote Emergency Recording/ Remote Relay Output Control, Remote settings Real-Time surveillance with remote Playback & File back up ( Triple on Remote ) Remote notification of event and automatic remote transmission of the alarm image activation. RS-232C/RS-422/RS-485 Communication PAN/TILT/ ZOOM/ FOCUS/AUX Control
- Remote Transmission PC Monitor and Analog Monitor
- PTZ Control & Port External devices IP or RS- 232 can be connected to as many of the cameras in the DVR System. (option)
- Video Output Give you the ability to check each camera remotely with nothing more than an internet browser.
- POS You have access and ability to control remotely up to 256 cameras in the system.
- DVR - Web Live Snapshot, Motion Search, Panoramic Search Event Log Viewer, Multiple site monitoring, Video popup, Image Zoom, Image Enhancement, Video Watermark
- DVR-Net Multi level, covered camera -remove from display or network
- Advanced Functions Enhanced log feature: system, motion, sensor, user, disk, loss E-mail notification on Video loss
- Security Desktop, Rock mount (option)
- Enclosure AC 100-120VAC 2A 50/60 Hz.
- Power



• Specification is subject to change without any prior notice  
Copyright © 2010 Navcom Corp. All rights reserved